

# DIN 6885 - A (Parallel Key Type A) -

DIN 6885-1 Type A. (l)

| d (mm)    | b (mm) | h (mm) | r (mm) | l (mm)                                |
|-----------|--------|--------|--------|---------------------------------------|
| 6 – 8     | 2      | 2      | 0.2    | 8, 10, 12, 14, 16, 18, 20             |
| 8 – 10    | 3      | 3      | 0.2    | 10, 12, 14, 16, 18, 20, 22, 25        |
| 10 – 12   | 4      | 4      | 0.4    | 12, 14, 16, 18, 20, 22, 25, 28        |
| 12 – 17   | 5      | 5      | 0.4    | 14, 16, 18, 20, 22, 25, 28, 32        |
| 17 – 22   | 6      | 6      | 0.4    | 16, 18, 20, 22, 25, 28, 32, 36        |
| 22 – 30   | 8      | 7      | 0.6    | 20, 22, 25, 28, 32, 36, 40, 45        |
| 30 – 38   | 10     | 8      | 0.8    | 25, 28, 32, 36, 40, 45, 50, 56        |
| 38 – 44   | 12     | 8      | 0.8    | 28, 32, 36, 40, 45, 50, 56, 63        |
| 44 – 50   | 14     | 9      | 1.0    | 32, 36, 40, 45, 50, 56, 63, 71        |
| 50 – 58   | 16     | 10     | 1.0    | 36, 40, 45, 50, 56, 63, 71, 80        |
| 58 – 65   | 18     | 11     | 1.2    | 40, 45, 50, 56, 63, 71, 80, 90        |
| 65 – 75   | 20     | 12     | 1.2    | 45, 50, 56, 63, 71, 80, 90, 100       |
| 75 – 85   | 22     | 14     | 1.5    | 50, 56, 63, 71, 80, 90, 100, 112      |
| 85 – 95   | 25     | 14     | 1.5    | 56, 63, 71, 80, 90, 100, 112, 125     |
| 95 – 110  | 28     | 16     | 1.5    | 63, 71, 80, 90, 100, 112, 125, 140    |
| 110 – 130 | 32     | 18     | 1.5    | 71, 80, 90, 100, 112, 125, 140, 160   |
| 130 – 150 | 36     | 20     | 1.5    | 80, 90, 100, 112, 125, 140, 160, 180  |
| 150 – 170 | 40     | 22     | 1.5    | 90, 100, 112, 125, 140, 160, 180, 200 |
| 170 – 200 | 45     | 25     | 1.5    | 100, 112, 125, 140, 160, 180, 200     |

: